

4MP Vandal-resistant Network IR Fixed Mini Dome



NEXLEN SOLE DISTRIBUTION
3 YEAR WARRANTY

4MP FULL HD

Small Size	Wide Angle	Optical 120dB True WDR	H.265	Video Analytic	15m Smart IR	Defog	250m PoE Distance	Pixel Analytic	Extreme Weather	IP66	IK10	Surge Protection

KEY FEATURES

Small Camera – It is a small, well appearance camera which is fit in different areas and buildings.

3-axis – It flexibly allows you to adjust the angle that the camera looks at the scene from.

Wide Angle – It allows to cover more area.

Optical 120dB True WDR – WDR function can ensure clear image with rich details when confronted with sharp lighting contrast, preventing dark or over-exposed image, ensuring great image quality.



WDR: OFF

WDR: ON

H.265 – Get **50% Reduction** on storage, bandwidth & bitrate with same image quality compared to H.264.



Smart IR illuminators to assist capturing objects in the dark even under **0 lux**, up to 49 feet (15 m) away.



Smart IR: OFF

Smart IR: ON

Video Analytic – Behavior Detection (Intrusion & Crossing Line), Intelligent Identification (Face Detection) and Statistical Analysis (People Counting).



Intrusion

Crossing Line



Face Detection

People Counting

SPECIFICATIONS

	IPC314SR-DVPPF28	IPC314SR-DVPPF36		IPC314SR-DVPPF28	IPC314SR-DVPPF36
Camera			Storage		
Sensor	1/3", 4 megapixel, progressive scan CMOS		Edge Storage	Micro SD, Up to 128 GB	
Shutter	Auto/Manual, 1/6~1/100,000 s		Network		
Lens	2.8mm	3.6mm	Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SIP, 802.1x	
Zoom/Focus	101.8°	76.8°	Compatible Integration	ONVIF, API	
Day/Night	IR-cut filter with auto switch (ICR)		Interface		
Min. Illumination	Colour: 0.02 Lux (F2.0, AGC ON) 0 Lux with IR		Audio I/O	Audio cable Input: impedance 35 kΩ; amplitude 2 V [p-p] Output: impedance 600 Ω; amplitude 2 V [p-p]	
S/N	>55 dB		Built-in Mic	Supported	
WDR	Optical WDR (up to 120dB)		Network	10M/100M Base-TX Ethernet	
Video			General		
Max. Resolution	2592 x 1520		Power	12 V DC, or PoE (IEEE802.3 af) Power consumption: 3~5W	
Video Compression	H.265, H.264, MJPEG		Dimensions (Ø x H)	Φ110 x 61 mm (Ø4.3" x 2.4")	
Capture Collect Mode	4MP (2592x1520): Max. 20 fps; 4MP (2560x1440): Max. 25 fps 3MP (2048x1520): Max. 30 fps; 1080P (1920x1080): Max. 30 fps		Weight	0.25 kg (0.55 lb)	
9:16 Corridor Mode	Supported		Working Environment	-35°C ~ +60°C (-31°F ~ +140°F), Humidity ≤ 95% RH (non-condensing)	
ROI	Supported		Vandal Resistant	IK10	
Video Streaming	Triple Streams		Ingress Protection	IP66	
OSD	Up to 8 OSDs				
Privacy Mask	Up to 8 areas				
Smart					
Behavior Detection	Intrusion, crossing line, motion detection				
Exception Detection	Audio detection				
Intelligent Identification	Face detection				
Statistical Analysis	People counting				

BRACKETS

